

Maîtrise d'Oeuvre 2003
03 - 05 JUNE 2003, PARIS

TITLE: CONCEPTION ECOLOGIQUE: QUELLES REALITES?

AUTHOR:

Dipl.-Ing. Harald Kraft,

Schmiljanstraße 7, 12161 Berlin.

Tel.: +49 - 30 - 851 66 16 / 85 96 11 94

Fax: +49 - 30 - 852 23 95

E-mail: kraft@ib-kraft.de

INTRODUCTION

In the 80's we had a very innovative phase concerning ecological housing and water management. Various experimental projects had been executed including decentralised waste water treatment and reuse. In the early 90's the access to waste water was blocked through the influence of the various lobbies. Fortunately this lobbies did not show much interest in dealing with storm water.

Until the mid-90's, all storm water was treated as contaminated surface runoff and diverted away in drainage systems. Drainage took precedence over infiltration. However, with the amendments in the state water laws, the water resource management objectives became reversed, and decentralised infiltration began to take precedence over drainage.

Storm water management in urban areas is basically subdivided into that for private lots and that for public property, including streets public squares, parks, or other open areas. It is primarily carried out through retention, reuse, and infiltration. Drainage of storm water as wastewater can now be seen as outdated. Storm water management intended to relieve the sewer network, infiltration to enhance groundwater recharge, and on a limited scale, the storm water collection for reuse, are finding increasingly more application in modern development projects.

In recent years new water management and treatment technologies have been developed and demonstrated in projects. This is true especially for singular concepts using either rainwater management technologies or wastewater treatment in different locations. No experience exists in the operation of integrated decentralised installations including the potential for energy generation. The goal of the recently initiated research on ECOSAN (ecological sanitation) is to gain experience in comprehensive design and implementation of singular technologies aiming at quasi-autark concepts requiring only a minimum of public water, waste and energy management services. These concepts should prove to function different types of settlements and urban structures as well as various regional conditions and demands.

THE EARLY INTEGRATED WATER CONCEPTS

Project Broendbystraße 40, Berlin-Lichterfelde

In 1985, the Berlin project "Ökohaus Broendbystraße 40" implemented, among other ecological technologies, a system of storm water harvesting and waste water treatment by means of a clivus multrum compost toilet (for toilet and organic household waste) and a root zone treatment plant for the grey water (10 PE). The treated effluent is reused for irrigation and the balance is discharged into an open water course. This system continues to be successfully operated today with very satisfactory results.

Project IBA Block 6, Berlin-Kreuzberg

Within the framework of the Internationale Bauausstellung (International Housing Exhibition), Berlin 1987, a pilot project in the area of experimental housing and town planning, with a strong ecological emphasis, was to be implemented in Block 6 under the auspices of the Federal Ministry of Regional Policy, Building and Urban Construction (Bundesministerium für Raumordnung, Bauwesen und Städtebau).

The objective of this demonstration project is maximum conservation of water resources through measures of reducing the drinking water consumption and environmental pollution caused by waste water. The rainwater was harvested in a rainwater pond.

The domestic sewage of 73 apartments in this pilot project is pumped from a collector pit outside the building into a root zone treatment plant for biological treatment. Research on the performance of the treatment plant has shown a reduction in the pollution load to below the standards of bathing water quality (of the EC), as well as successful reuse of the effluent for irrigation and toilet flushing. This project has received an award from the President of the Federal Republic of Germany in a national competition.

**STORMWATER HARVESTING AND REUSE PROJECTS IN GERMANY
THE DESIGN OF ZERO RUNOFF SETTLEMENT****Project Berliner Straße 88, Berlin-Zehlendorf**

In 1992 the construction of project Berliner Straße 88 was begun. The storm water from 160 housing units is collected in three cisterns making up a total storage capacity of 650 m³. The water is then reused for irrigation. The runoff is discharge into an artificial water course and a storm water pond of 1.000 m² (1.500 m³, max, depth 3 m). The pond water is recycled through the water course by solar and wind energy and continuously cleaned in a root zone treatment plant (the water percolates horizontally to the rootzone of a 1 m depth reed bed). The excess water is infiltrated through ground water recharge units. No storm water leaves the premises.

Project Schweriner Hof, Berlin-Hellersdorf

This project was recognised as an exemplary model of an ecological project in the Habitat II Conference in Istanbul in 1996. The storm water runoff from the roofs is stored in a 600 m³ cistern and reused for irrigation and for the regulation of a rain water pond.

The external water, as well as the surface runoff, is infiltrated through an infiltration trench system into the ground, which was actually declared to be unfit for infiltration.

Project Landsberger Tor, Berlin-Marzahn

In this large project (30 ha, 1.800 units), the storm water runoff from the roofs is infiltrated into an infiltration trench system. The storm water runoff from the roads is collected in a conventional storm water drain and discharged into a storm water treatment and infiltration facility, located in a public park. The facility consists of a separate unit for mechanical treatment, a rain water lake, and a root zone treatment plant for the biological treatment. The outflow is infiltrated through ditches. The total surface area of the facility is 5.000 m². The project design is the outcome of an international competition.

Project "Teltow-Mühlendorf"

This project area is 29 ha, comprising 1.800 housing units.

Terrain Modelling

This newly developed concept assumes that all of the storm water and the necessary excavation is to stay on the project site. Using the displaced earth (250 000 m³), the terrain has been modelled so that the surface water can be diverted to a centrally located pond, resulting in a rise of about 1 m in the ground level in the centre of the project. A considerable environmental stress has been prevented by not hauling away the excavated earth, which would have require approx. 25 000 truck loads.

Storm Water Disposal for Traffic Ways

The major goal of this design is to minimise the interference of the natural water regime within the project area. In spite of the high percentage of paved and otherwise sealed areas, the precipitation remains within the boundaries of the project. The storm water runoff from sidewalks, bicycle paths, parking lanes, pedestrian walkways, green areas and playgrounds is conveyed to the subsoil through local infiltration. The runoff from the streets is intercepted in lateral gutters and conveyed to three storm water purification facilities and, after being extensively biologically treated, fed to a central storm water pond. Surplus storm water is infiltrated when complete filling of the pond forces water over the edge into infiltration trenches located in the banks. The overflow is also biologically treated prior to the infiltration in vegetated filters.

Storm Water Disposal on Residential Lots

The precipitation from all rooftops is stored in cisterns and from there made available to the residents to be used as non-potable water substitution. The surplus water is to be led to infiltration trenches. The pond water will be circulated through four natural-looking channels (flowing brooks), which run through the residential areas. The resulting cooling effect on the immediate surroundings, as well as the enhancement of the living conditions through simultaneous aeration of the lake, are the primary goals of the design concept.

Summary of Technical Data

Catchment Area	A [in ha]	Precipitation* [in m³/yr.]	Project Data	Quantity Unit
Size of Project Area (approx.):	27,9	163.634	Inhabitants:	3.000
Area covered by streets	5,8	33.841	Living units	1.850
Including:			Infiltration trench length (not including bank of pond)	9.000 m
bicycle paths and sidewalks	1,9	10.909	public	6.000 m
street greenery	0,7	3.812	private	3.000 m
public streets	3,8	22.404	Cistern volume	4.500 m³
private streets	2,0	11.437	Non-potable water capacity	290 m³/h
Roof area	4,5	26.393	Volume of lake	23.000 m³
Open areas (public parks)	1,6	9.091	Surface area of lake	8.600 m²
Open areas (private)	16,1	94.309	Surface of rootzone treatment facilities	1500 m²

*...average year

Project "Former Airfield Böblingen-Sindelfingen"

In this 85 ha project, the entire storm water runoff is proposed to be collected, treated and reused as a substitute for drinking water used in recreation, irrigation, toilet flushing, washing machines and still further uses where drinking water quality is not required. The excess water is discharged to a river bed. The basic aim here is that all of the storm water will be reused within the project area.

THE PRESENT DESIGN OF ECOLOGICAL SANITATION

Project "International City of Auroville", India

The International City of Auroville is designed by the French Architect Roger Anger.

This township is to inhabit 50.000 people within a circular area with a diameter of 2,5 km, and be surrounded by a 1,25 km wide greenbelt.

The geographic centre of the township is located on a gentle hill, 52 m above sea level, 5 km from the coast of the Andaman Sea, and 200 km south of Madras. When the first settlers arrived, the hill was devastated by centuries of deforestation. Huge gullies had been caved out. The land had been cleared and the red earth was exposed to the torrential monsoon rains. The construction of Auroville began in the centre, which is to be created into a park with a spherical building, 30 m in diameter, an amphitheatre, and an old banian tree surrounded by a large lake. In the early 1970's, the place was not fit for human life, with no shade and no water. The first settlers had to control the erosion by "bundings" and

reforestation, as well as provide the basic infrastructure and water supply. This has just recently been achieved. In the meantime, the population in the surrounding areas has grown, along with their ability to extract groundwater.

Since the early 1990's, sea water intrusion into the coastal aquifers has been reported.

Under this threat, an alternative water management scheme was developed in 1992 in order to safeguard the very existence of the city. It is planned to base the entire water supply on the precipitation. The rain water is to be harvested from the roofs and stored in cisterns. The remaining surface runoff, including that from the roads, is to be captured and stored in large reservoirs within the greenbelt. After purification, it will be lifted up to the large central lake. After further purification in the lake, the overflow will be infiltrated beneath the park into the first aquifer which lies above sea level. From there, the water can be tapped by wells throughout the city. The harvested storm water is not sufficient to meet the full demand for irrigation. Therefore, the entire waste water has to be treated to meet bathing water quality standards and reused for the irrigation of agricultural lands within the greenbelt.

Project Werbellinsee (ex "Pioneer Republic Wilhelm Pieck")

The Werbellinsee project offers place for about 1.100 visitors in around 30 guesthouses. The project was founded by the former German Democratic Republic in 1952 and was named after its founder and the first president of the German Democratic Republic, "Pioneer Republic Wilhelm Pieck". Today the project site is used for recreation by the youth (European Meeting Place for Young People), sport, vocational education and international meetings. The area of 200 ha at the marvellous Werbellin lake is covered by 100 ha of forest. The built up area is protected under the monument protection law and comprises of 42.000 m² floor area. The project was designed by Richard Paulick¹.

The aim of reconstructing parts of the technical infrastructure is to revive the original autarkic concept of water and energy supply and management.

The research and development project will demonstrate new concepts, technologies and products for minimising wastewater, separation of faeces, urine and water and reusing treated wastewater. Furthermore the potentials of reuse of rainwater can be demonstrated. The decentralised generation of electricity and heat will include the use of organic wastes and leftover wood from logging activities.

The project comprises of the following elements:

1. Drinking water supply by rehabilitating the existing deep ground water wells on the site,
2. Minimising wastewater by modern sanitation technologies (separation toilets, dry toilets, separation of urine and faeces, urine will be used for soil improvement).
3. Remaining wastewater being treated at the treatment plant on the project site (anaerobic treatment of sludge, trickling filter, rootzone treatment and membrane technology) for reuse in irrigation and toilets.
4. Rainwater run-off collected in cisterns of different dimension for drinking water substitution (baths, toilet flushing, washing machines) and for groundwater recharge.
5. Anaerobic treatment of organic waste (especially from the restaurants), use of methane gas and sludge from waste water treatment for energy production.
6. Block heating and power generating plant that produces energy from renewable resources (methane gas, chopped wood, wood pellets)

The project is selected for the participation in the Federal Research Program "Decentralised Water Supply and Sanitary Systems".

¹ Richard Paulick, born 1903, affiliated with BAUHAUS since 1924, founder of Socialist Labour Party in 1933, emigrated to Shanghai, 1942 professor for architecture at the University of Shanghai and 1945 town planning director of Shanghai, 1949 member of Institute for Construction under Hans Sharoun, among other works architect of parts of Karl-Marx-Avenue in former East Berlin

Project B31, Reinbek – “Living Space”

The project area of 4,2 ha offers the space for about 200 people in 40 - 50 flats.

The project will demonstrate new concepts, technologies and products for minimising wastewater, separation of faeces, urine and water and reusing treated wastewater. Furthermore the potentials of reuse of rainwater can be demonstrated. The decentralised generation of electricity and heat will include the use of organic wastes and leftover wood from logging activities.

The project comprises of the following elements:

1. Drinking water supply by rehabilitating the existing deep ground water well on the site,
2. Minimising wastewater by modern sanitation technologies (separation toilets, dry toilets, separation of urine and faeces, urine will be used for soil improvement)
3. Remaining wastewater being treated at the treatment plant on the project site (anaerobic treatment of sludge, rootzone treatment) for reuse in irrigation.
4. Rainwater run-off collected in a pond and in a balancing tank for drinking water substitution for toilet flushing, washing machines and for groundwater recharge.
5. Anaerobic treatment of organic waste, use of methane gas and sludge from waste water treatment for energy production.
6. Block heating and power generating plant that produces energy from renewable resources (methane gas, wood pellets, solar energy)

THE FUTURE

The future development will be towards the autarcic building in a city without sewers and pipes.